



Product Data Sheet

M2 Lube

PIPE ON PIPE LUBE

Description

M2 Lube is a High-Tech lubricant concentrate specifically developed for coil tubing and highly deviated or horizontal drilling applications. M2 Lube has a high affinity for metal surfaces and will adhere tenaciously to drill pipe and drill collars. This guarantees that the lubricant will be concentrated exactly where it is needed, between the pipe and the formation. The pipe can then slide effectively without excessive loss of weight to the bit. M2 Lube eliminates torque and drag, prevents differential sticking, and protects the drill pipe from corrosion.

Applications

The extreme efficiency of this product allows for low use levels. For a typical 800–1000 bbl system, add 1–1/2 drums slowly (one drum per hour). Maintain the system

as needed while drilling. Always add the product s-l-o-w-l-y into the suction pit as close to the suction line as possible.

Shipping and Handling

M2 Lube is available in 5-gallon pails, 55-gallon drums and bulk tank trucks. Consult the SDS, safety poster, and/or product label before use. Use proper personal protective equipment as advised. Handle with care to avoid skin and eye contact. If contact occurs flush with large amounts of fresh water.

Typical Physical Properties

Appearance	Brown Liquid
Flash Point	>93°C / >200°F
Odor	Mild
pH (Neutrality)	4–7
Vapor Density	6.8

*All weights are approximate. The information and data contained herein are believed to be accurate and reliable. Bri-Chem Supply Corp. makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information.